

**Modelo 38-N**

**Model 38-N**



Máquina remachadora neumática para aplicar remaches semitubulares para balata y clutch.

Pneumatic rivet setting machine. Applies brake and clutch semitubulars rivets.

- **Diametro Máximo:** 1/4" 6.35 mm
- **Largo Máximo:** 1-1/2" 38.1 mm
- **Profundidad de Garganta:** 7" 177.80 mm
- **Carrera:** 5/8" 15.87 mm
- **Peso Neto:** 165Lbs. 75 Kgs.
- **Presión de aire:** 113 Lbs./in<sup>2</sup> 8 Kg./m<sup>2</sup>

- **Maximum Diameter:** 1/4"
- **Maximum Length:** 1-1/2"
- **Throat Depth:** 7"
- **Stroke:** 5/8"
- **Net Weight:** 165 Lbs.
- **Air Pressure:** 113 Lbs/in<sup>2</sup>

Cuenta con las siguientes estaciones de trabajo:

Dispositivo para remachar

Dispositivo para quitar remache

Featuring the following work stations:

Riveting device

Rivet removal device

Modelo 912

Model 912



Máquina remachadora electromecánica con alimentador, para aplicar remaches semitubulares y ojillos.

Motor powered rivet setting machine with hopper. Applies semitubular rivets and eyelets.

- Diámetro Máximo: 3/16" 4.76 mm
- Largo Máximo: 15/16" 23.81 mm
- Profundidad de Garganta: 12" 304.80 mm
- Carrera: 2 1/2" 63.50 mm
- Motor: 1/2 hp 1/2 hp
- Peso Neto: 565 Lbs. 257 Kgs.

- Maximum Diameter: 3/16"
- Maximum Length: 15/16"
- Throat Depth: 12"
- Stroke: 2 1/2"
- Motor: 1/2 hp
- Net Weight: 565 Lbs.

Modelo 912 EL

Model 912 EL



Máquina remachadora electromecánica con alimentador, para aplicar remaches Semitubulares y ojillos.

Motor powered rivet setting machine with hopper. Applies semitubular rivets and eyelets.

- Diámetro Máximo: 3/16" 4.76 mm
- Largo Máximo: 15/16" 23.81 mm
- Profundidad de Garganta: 12" 304.80 mm
- Carrera: 2 1/2" 63.50 mm
- Motor: 1/2 hp 1/2 hp
- Peso Neto: 565 Lbs. 257 Kgs.

- Maximum Diameter: 3/16"
- Maximum Length: 15/16"
- Throat Depth: 12"
- Stroke: 2 1/2"
- Motor: 1/2 hp
- Net Weight: 565 Lbs.

**Modelo 914-N**

**Model 914-N**



Máquina remachadora neumática para aplicar remaches semitubulares para balata y clutch.

Pneumatic rivet setting machine. Applies brake and clutch semitubulars rivets.

- Diametro Máximo: 1/4" 6.35 mm
- Largo Máximo: 1-1/2" 38.1 mm
- Profundidad de Garganta: 7" 177.80 mm
- Carrera: 5/8" 15.87 mm
- Peso Neto: 160.6Lbs. 73 Kgs.
- Presión de aire: 113 Lbs./in<sup>2</sup> 8 Kg./m<sup>2</sup>

- Maximum Diameter: 1/4"
- Maximum Length: 1-1/2"
- Throat Depth: 7"
- Stroke: 5/8"
- Net Weight: 160.6 Lbs.
- Air Pressure: 113 Lbs/in<sup>2</sup>

Modelo 450

Model 450



Máquina remachadora electromecánica con alimentador para aplicar remaches semitubulares y ojillo.

Motor powered rivet setting machine with hopper. Applies semitubular rivets and eyelets

- Diametro Máximo: 9/64" 3.57 mm
- Largo Máximo: 3/4" 19.05 mm
- Profundidad de Garganta: 6" 152.40 mm
- Carrera: 2" 50.80 mm
- Motor: 1/4hp 1/4 hp
- Peso Neto: 268 Lbs. 122 Kgs.

- Maximum Diameter: 9/64"
- Maximum Length: 3/4"
- Throat Depth: 6"
- Stroke: 2"
- Motor: 1/4 hp
- Net Weight: 268 Lbs.

Modelo 450-B

Model 450-B



Máquina electromecánica con doble alimentador para aplicar botones, hembra jeans y remaches rápidos.

- Profundidad de Garganta: 6" 152.40 mm
- Carrera: 2" 50.80 mm
- Motor: 1/4hp 1/4 hp
- Peso Neto: 286 Lbs. 130 Kgs.

Motor powered button setting machine with two hoppers. Also applies burrs and quick rivets.

- Throat Depth: 6"
- Stroke: 2"
- Motor: 1/4 hp
- Net Weight: 286 Lbs.